

Article	Malossi designation	Voltage V	Cap. Ah (10h)	Cap. Ah (20h)	CCA A -18°C 0°F	Dimensions (± 2mm)			Assembly Drawing	Terminal drawings				Charging guide		
						L	W	H		Front	Side	Top	3D	Standard	Quick	
4418916	MB4L-B	12	5	5.3	50	120	70	92	-	+					0.4A x 5-10h	2A x 1h
4418917	MB9-B (12N9-4B-1)	12	9	9.5	115	135	75	139	+	-					0.9 A x 5-10h	4.5 A x 1h
4419165	MB10L-A2/B2	12	11	11,6	120	133	90	145	-	+					1.1 A x 5-10h	5.5 A x 1h
4418918	MTX5L-BS	12	4	4.2	80	113	70	105	-	+					0.4 A x 5-10h	2 A x 1h
4418919	MTX7L-BS	12	6	6.3	100	113	70	130	-	+					0.6 A x 5-10h	3 A x 1h
4418920	MTX7A-BS	12	6	6.3	90	150	87	93	+	-					0.6 A x 5-10h	3 A x 1h
4418921	MTX9-BS	12	8	8.4	135	150	87	105	+	-					0.8 A x 5-10h	4 A x 1h
4419166	MT12A-BS	12	10	10,5	175	150	88	105	+	-					1 A x 5-10h	5 A x 1h
4418922	MTX12-BS	12	10	10.5	180	150	87	130	+	-					1 A x 5-10h	5 A x 1h
4418923	MTX14-BS	12	12	12.6	200	150	87	145	+	-					1.2 A x 5-10h	6 A x 1h
4418924	MTZ7S	12	6	6.3	130	113	70	105	-	+					0.6 A x 5-10h	3 A x 1h
4419168	MTZ8V	12	7	7.4	120	113	70	130	-	+					0.7 A x 5-10h	3.5 A x 1h
4419167	MT7B-4	12	6.5	6.8	110	150	65	93	+	-					0.65 A x 5-10h	3.25 A x 1h
4419169	MT9B-4	12	8	8.4	120	150	68	105	+	-					0.8 A x 5-10h	4 A x 1h
4418925	MTZ12S	12	11	11.6	210	150	88	110	+	-					1.1 A x 5-10h	5.5 A x 1h